Carbonate awnings



Translucent | Lightweight | Tough | Longlasting | Leakproof | Versatile
















Above: 50 x 50 beam for larger arm spans

flat window awnings

- 8mm twin wall polycarbonate available in 5 designer colours
- Extruded aluminium joining sections available in 4 standard colours
- Special frame colours on request
- Maximum projection is 1600mm (arms every 2.2m)
- Sturdy 38 x 25 x 2.0mm arms with die cut wall and arm brackets
- Suitable for window and door coverings
- Sheet panels are 725mm wide (including joining strip)










bullnose window awnings

- 8mm twin wall polycarbonate available in 5 designer colours
- Extruded aluminium joining sections available in 4 standard colours
- Special frame colours on request
- Maximum projection is 1600mm. (arms every 2.2m)
- Sturdy 38 x 25 x 2.0mm arms with die cut wall and arm brackets
- Suitable for window and door coverings
- Sheet panels are 725mm wide (including joining strip)








domus window awnings


- 8mm twin wall polycarbonate available in 5 designer colours
- Extruded aluminium joining sections available in 4 standard colours
- Special frame colours on request
- Maximum projection is 1600mm. (arms every 2.2m)
- Sturdy 38 x 25 x 2.0mm arms with die cut wall and arm brackets
- Suitable for window and door coverings
- Sheet panels are 725mm wide (including joining strip)




SKIN	X	Υ	RISE
960	670	670	80
1160	800	800	120
1450	980	980	185
1600	1075	1075	225

All measurements in mm









barrel vault awnings

- 8mm twin wall polycarbonate available in 5 designer colours
- Extruded aluminium joining sections available in 4 standard colours
- Special frame colours on request
- Maximum projection is 1050mm
- Sturdy 50 x 50 x 2.5mm arms with welded base plate fixing
- Suitable for window and door coverings
- Maximum radius 1400mm





 An angle piece for 1050mm brackets is available for high wind areas (extra cost involved)



gabled window awnings

- 8mm twin wall polycarbonate available in 5 designer colours
- Extruded aluminium joining sections available in 4 standard colours
- Special frame colours on request
- Maximum projection is 1050mm
- Sturdy 50 x 50 x 2.5mm arms with welded base plate fixing
- Suitable for window and door coverings
- Pitch can be varied depending on bracket position








cantilevered awnings

(flat & bullnosed)

- 8mm twin wall polycarbonate available in 5 designer colours
- Extruded aluminium joining sections available in 4 standard colours
- Special frame colours on request
- Maximum projection is 2600mm
- Sturdy welded frame trusses to engineer specifications
- Suitable for patio covers
- Pitch set at 5 degree fall but can be pre welded to any angle requested



clearlite awnings

- 3.00mm solid polycarbonate available in clear/grey/bronze and opal sheet.
- Projections up to 1220mm.
- Sturdy 38mm x 25mm arm supports.
- special frames colours on request.





louvred awnings

- Aluminium slatted panels using either 65mm x 16mm RHS slat or 85mm eliptical
- Slats are fixed at 57 degrees
- Available in any powdercoated colour
- Available in welded
- cantilever or arm supported awnings
- Available as window shades and privacy screens







colour range

8mm Twinwall	Light	Shading transmission
Clear	86%	72%
Grey	42%	45%
Bronze	42%	45%
Solar Metallic	25%	28%
Solar Ice	20%	25%

frame colour

- · Pearl White · Primrose
- Anodic Bronze
 Satin Black
- · Special colours on request

water diversion



CARBOLITE gutter attachment



CARBOLITE diverter kit (used only for awnings up to 3m²)

Approved distributor